

Shrink Tubing

Provides Insulated, Abrasion Resistant & Flame Retardant Covering
 Acts As Strain Relief When Used Over Wire/Terminal Connections
 Color Code Polarity of Battery Cables On Battery Terminal Connections
 Helps Prevent Corrosion



INSTALLATION:
 Slide Tubing Over Wire
 Crimp Terminal On Wire
 Apply Heat 230°F to 348°F
 (110°C to 120°C)
 Cool For Tough Insulation



*Tubing Measured
 By Inside Diameter
 Before Shrinking*

SINGLE WALL SHRINK TUBING

Flexible Polyolefin Single Wall Tubing
 Multi-Purpose & Flame Retardant
 Shrink Ratio 2 to 1
 Operating Temperature:
 -67°F to 275°F (-55°C to 135°C)

WATERPROOF SHRINK TUBING

Semi-Flexible Polyolefin Dual Wall
 Inner Adhesive Wall Melts & Flows
 While Outer Wall Shrinks
 Moisture Proof Upon Cooling
 Shrink Ratio 3 to 1
 Operating Temperature:
 -49°F to 257°F (-45°C to 125°C)



Kits Available (Page 7)
Single Wall:
 #0003-SR, #0003-SRB

Waterproof:
 #0003-SW

*100' AA
 Cardboard Spools*



SINGLE WALL SHRINK TUBING COMBINATION PACK

Package of 6" or 2" Pieces
 1/8" 3/16" 1/4" 3/8" Diameter Tubing

Part #	Qty
8226C	4-6"
8226H	10-2"
8226PT	4-6"
8226KT	10-2"
8226QT	5-2"



		BLACK		RED	
I.D.	Part #	Qty	Part #	Qty	Part #
1/8"	8219AA	100'	--	--	
1/8"	8219A	4'	8250A	4'	
1/8"	8219C	4-6"	8250C	4-6"	
1/8"	8219PT	4-6"	8250PT	4-6"	
3/16"	8220AA	100'	--	--	
3/16"	8220A	4'	8251A	4'	
3/16"	8220C	4-6"	8251C	4-6"	
3/16"	8220PT	4-6"	8251PT	4-6"	
1/4"	8221AA	100'	8252AA	100'	
1/4"	8221A	4'	8252A	4'	
1/4"	8221C	4-6"	8252C	4-6"	
1/4"	8221PT	4-6"	8252PT	4-6"	
3/8"	8222AA	100'	8253AA	100'	
3/8"	8222A	4'	8253A	4'	
3/8"	8222C	4-6"	8253C	4-6"	
3/8"	8222PT	4-6"	8253PT	4-6"	
1/2"	8223AA	100'	--	--	
1/2"	8223A	4'	8254A	4'	
1/2"	8223C	4-6"	8254C	4-6"	
1/2"	8223PT	4-6"	8254PT	4-6"	
3/4"	8224AA	100'	--	--	
3/4"	8224A	4'	8255A	4'	
3/4"	8224C	4-6"	8255C	4-6"	
3/4"	8224PT	4-6"	8255PT	4-6"	
1"	8225AA	100'	--	--	
1"	8225A	4'	8256A	4'	
1"	8225C	4-6"	8256C	4-6"	
1"	8225PT	4-6"	8256PT	4-6"	



		BLACK		RED	
I.D.	Part #	Qty	Part #	Qty	Part #
1/8"	8229A	4'	8259A	4'	
1/8"	8229C	4-6"	8259C	4-6"	
1/8"	8229PT	4-6"	8259PT	4-6"	
3/16"	8230A	4'	8260A	4'	
3/16"	8230C	4-6"	8260C	4-6"	
3/16"	8230PT	4-6"	8260PT	4-6"	
1/4"	8231A	4'	8261A	4'	
1/4"	8231C	4-6"	8261C	4-6"	
1/4"	8231PT	4-6"	8261PT	4-6"	
3/8"	8232A	4'	8262A	4'	
3/8"	8232C	4-6"	8262C	4-6"	
3/8"	8232PT	4-6"	8262PT	4-6"	
1/2"	8233A	4'	8263A	4'	
1/2"	8233C	4-6"	8263C	4-6"	
1/2"	8233PT	4-6"	8263PT	4-6"	
3/4"	8234A	4'	8264A	4'	
3/4"	8234C	4-6"	8264C	4-6"	
3/4"	8234PT	4-6"	8264PT	4-6"	
1"	8235A	4'	8265A	4'	
1"	8235C	4-6"	8265C	4-6"	
1"	8235PT	4-6"	8265PT	4-6"	
1-1/4"	8236A	4'	8266A	4'	
1-1/4"	8236C	4-6"	8266C	4-6"	
1-1/4"	8236PT	4-6"	8266PT	4-6"	
1-1/2"	8237A	4'	8267A	4'	
1-1/2"	8237C	4-6"	8267C	4-6"	
1-1/2"	8237PT	4-6"	8267PT	4-6"	

Carburetor Caps



*Kits Available
 (Page 4)*



Black EPDM Rubber Vacuum Caps
 Max Temperature 250°F (121°C)

Listed Sizes Are Approximate OD of Item To Be Capped

O.D.	Part #	Qty	Part #	Qty	Part #	Qty
1/8"	7030A	500	7030C	25	7030PT	25
3/16"	7031A	500	7031C	25	7031PT	25
1/4"	7032A	500	7032C	20	7032PT	20
5/16"	7033A	500	7033C	15	7033PT	15
3/8"	7034A	500	7034C	10	7034PT	10
Assorted Pack			7036C	10	7036PT	10



*Kits Available
 (Page 4)*



Flexible Vinyl Tips
 Temperature Rating:
 -22°F to 200°F (-38°C to 93°C)

I.D.	Color	Length	Part #	Qty	Part #	Qty	Part #	Qty
1/8"	Black	5/8"	7020A	1000	7020C	50	7020KT	40
3/16"	White	5/8"	7021A	1000	7021C	25	7021KT	20
1/4"	Red	3/4"	7022A	1000	7022C	20	7022KT	13
5/16"	Blue	3/4"	7023A	1000	7023C	15	7023KT	9
3/8"	Yellow	7/8"	7024A	1000	7024C	10	7024KT	6
Assorted Pack	Mixed		7029C	40	7029D	19	7029KT	17
Assorted Pack	Mixed		7029M	9	7029PT	40	7029QT	9

All Items with QT, KT, GT or PT Suffix are Clam Shell Program Items.