

Chassis Clips

Spring Steel Push-On Wire Clips
 Black Phosphate Finish
 Spring Tension Holds Clip In Place On Frame
 While Securing Wires To Frame Surface
 Clips Measured by Frame Thickness



| Frame | Part # | Qty | Part # | Qty |
|-------|--------|-----|--------|-----|
| 3/16" | 7060A | 200 | — | — |
| 3/16" | 7060C | 25 | 7060PT | 25 |
| 3/16" | 7060M | 3 | 7060QT | 3 |
| 1/4" | 7061A | 200 | — | — |
| 1/4" | 7061C | 15 | 7061PT | 15 |
| 1/4" | 7061M | 2 | 7061QT | 2 |
| 3/8" | 7062A | 100 | — | — |
| 3/8" | 7062C | 10 | 7062PT | 10 |
| 3/8" | 7062M | 2 | 7062QT | 2 |

Winged Clips

Black Polypropylene Clips
 Secures Wiring Harness or Convolution Tubing
 To Sheet Metal Backing
 Clips Measured By Tubing Diameter
 1/4" Drill Hole - .15" Max Material Thickness



| Diameter | Part # | Qty |
|----------|--------|-----|
| 3/8" | 5101A | 50 |
| 3/8" | 5101C | 4 |
| 3/8" | 5101PT | 4 |
| 1/2" | 5102A | 50 |
| 1/2" | 5102C | 4 |
| 1/2" | 5102PT | 4 |
| 3/4" | 5103A | 50 |
| 3/4" | 5103C | 3 |
| 3/4" | 5103PT | 3 |

Nylon Clamps

Durable Natural or Black Nylon Clamp For Channeling Wire
 Clamps Measured By Inside Diameter When Closed
 Bottom Hole Elongated For Easy Alignment
 Operating Temperature -60°F to 185°F (-51°C to 85°C)

*Kits Available
 (Page 2)*



**PACKAGE OF ASSORTED SIZES
 Natural**

| Part # | Qty |
|--------|-----|
| 7115C | 22 |
| 7115PT | 22 |



NATURAL
 3/8" Wide Clamp
 .190" Screw Hole - #10 Stud

| I.D. | Part # | Qty | Part # | Qty |
|-------|--------|-----|--------|-----|
| 1/8" | 7118A | 500 | — | — |
| 1/8" | 7118C | 40 | 7118PT | 40 |
| 1/8" | 7118M | 7 | 7118QT | 7 |
| 3/16" | 7119A | 500 | — | — |
| 3/16" | 7119C | 35 | 7119PT | 35 |
| 3/16" | 7119M | 7 | 7119QT | 7 |
| 1/4" | 7120A | 500 | — | — |
| 1/4" | 7120C | 35 | 7120PT | 35 |
| 1/4" | 7120M | 7 | 7120QT | 7 |
| 5/16" | 7121A | 500 | — | — |
| 5/16" | 7121C | 22 | 7121PT | 22 |
| 5/16" | 7121M | 6 | 7121QT | 6 |

NATURAL
 1/2" Wide Clamp
 .190" Screw Hole - #10 Stud

| I.D. | Part # | Qty | Part # | Qty |
|------|--------|-----|--------|-----|
| 3/8" | 7122A | 500 | — | — |
| 3/8" | 7122C | 18 | 7122PT | 18 |
| 3/8" | 7122M | 6 | 7122QT | 6 |
| 1/2" | 7124A | 500 | — | — |
| 1/2" | 7124C | 12 | 7124PT | 12 |
| 1/2" | 7124M | 4 | 7124QT | 4 |
| 5/8" | 7126A | 250 | — | — |
| 5/8" | 7126C | 10 | 7126PT | 10 |
| 5/8" | 7126M | 3 | 7126QT | 3 |
| 3/4" | 7128A | 250 | — | — |
| 3/4" | 7128C | 5 | 7128PT | 5 |
| 3/4" | 7128M | 2 | 7128QT | 2 |
| 1" | 7130A | 250 | — | — |
| 1" | 7130C | 4 | 7130PT | 4 |
| 1" | 7130M | 1 | 7130QT | 1 |



BLACK
 3/8" Wide Clamp
 .190" Screw Hole - #10 Stud

| I.D. | Part # | Qty | Part # | Qty |
|-------|--------|-----|--------|-----|
| 1/8" | 7138A | 500 | — | — |
| 1/8" | 7138C | 40 | 7138PT | 40 |
| 1/8" | 7138M | 7 | 7138QT | 7 |
| 3/16" | 7139A | 500 | — | — |
| 3/16" | 7139C | 35 | 7139PT | 35 |
| 3/16" | 7139M | 7 | 7139QT | 7 |
| 1/4" | 7140A | 500 | — | — |
| 1/4" | 7140C | 35 | 7140PT | 35 |
| 1/4" | 7140M | 7 | 7140QT | 7 |
| 5/16" | 7141A | 500 | — | — |
| 5/16" | 7141C | 22 | 7141PT | 22 |
| 5/16" | 7141M | 6 | 7141QT | 6 |

BLACK
 1/2" Wide Clamp
 .190" Screw Hole - #10 Stud

| I.D. | Part # | Qty | Part # | Qty |
|------|--------|-----|--------|-----|
| 3/8" | 7142A | 500 | — | — |
| 3/8" | 7142C | 18 | 7142PT | 18 |
| 3/8" | 7142M | 6 | 7142QT | 6 |
| 1/2" | 7144A | 500 | — | — |
| 1/2" | 7144C | 12 | 7144PT | 12 |
| 1/2" | 7144M | 4 | 7144QT | 4 |
| 5/8" | 7146A | 250 | — | — |
| 5/8" | 7146C | 10 | 7146PT | 10 |
| 5/8" | 7146M | 3 | 7146QT | 3 |
| 3/4" | 7148A | 250 | — | — |
| 3/4" | 7148C | 5 | 7148PT | 5 |
| 3/4" | 7148M | 2 | 7148QT | 2 |
| 1" | 7150A | 250 | — | — |
| 1" | 7150C | 4 | 7150PT | 4 |
| 1" | 7150M | 1 | 7150QT | 1 |

Rubber Insulated Clamps

Secures Wiring To Body or Frame
 Flexible Neoprene Cushion
 Holds Lines Firmly In Place While
 Protecting From Shock, Abrasion & Vibration
 Clamps Measured By
 Inside Diameter When Closed



*Rugged
 Long Lasting*



1/4" MOUNTING HOLE
 Aluminum - 1/2" Metal Width

| I.D. | Part # | Qty | Part # | Qty | Part # | Qty |
|----------|--------|-----|--------|-----|--------|-----|
| Assorted | — | — | 7300C | 17 | 7300PT | 17 |
| 1/4" | 7314A | 100 | 7314C | 20 | 7314PT | 20 |
| 3/8" | 7315A | 100 | 7315C | 20 | 7315PT | 20 |
| 1/2" | 7316A | 100 | 7316C | 15 | 7316PT | 15 |
| 5/8" | 7317A | 100 | 7317C | 12 | 7317PT | 12 |
| 3/4" | 7318A | 100 | 7318C | 10 | 7318PT | 10 |
| 7/8" | 7319A | 100 | 7319C | 8 | 7319PT | 8 |
| 1" | 7320A | 100 | 7320C | 6 | 7320PT | 6 |
| 1-1/8" | 7321A | 100 | 7321C | 6 | 7321PT | 6 |
| 1-1/4" | 7322A | 100 | 7322C | 4 | 7322PT | 4 |
| 1-3/8" | 7323A | 100 | 7323C | 4 | 7323PT | 4 |
| 1-1/2" | 7324A | 100 | 7324C | 4 | 7324PT | 4 |
| 1-5/8" | 7325A | 100 | 7325C | 3 | 7325PT | 3 |
| 2" | 7327A | 100 | 7327C | 2 | 7327PT | 2 |

3/8" MOUNTING HOLE
 Steel with Zinc Plating - 5/8" Metal Width

| I.D. | Part # | Qty | Part # | Qty | Part # | Qty |
|--------|--------|-----|--------|-----|--------|-----|
| 1/4" | 7514A | 100 | 7514C | 15 | 7514PT | 15 |
| 3/8" | 7515A | 100 | 7515C | 12 | 7515PT | 12 |
| 1/2" | 7516A | 100 | 7516C | 10 | 7516PT | 10 |
| 5/8" | 7517A | 100 | 7517C | 8 | 7517PT | 8 |
| 3/4" | 7518A | 100 | 7518C | 8 | 7518PT | 8 |
| 7/8" | 7519A | 100 | 7519C | 8 | 7519PT | 8 |
| 1" | 7520A | 100 | 7520C | 7 | 7520PT | 7 |
| 1-1/4" | 7522A | 100 | 7522C | 4 | 7522PT | 4 |
| 1-1/2" | 7524A | 100 | 7524C | 3 | 7524PT | 3 |
| 2" | 7525A | 100 | 7525C | 2 | 7525PT | 2 |
| 2-1/2" | 7527A | 100 | 7527C | 2 | 7527PT | 2 |
| 3" | 7529A | 100 | 7529C | 1 | 7529PT | 1 |
| 4" | 7531A | 100 | 7531C | 1 | 7531PT | 1 |



Kit Available - #0003-RC (Page 4)

All Items with QT, KT, GT or PT Suffix are Clam Shell Program Items.