

Electrical Tape



#3460C
20 Roll Display Box
Shelf or Counter Display

Pop-Up Display Box!

Tru-Grip All Weather PICO Black Vinyl Tape
Excellent Adhesion In All Types Of Weather
UL & CSA Approved
For Use At Not More Than 80°C (176°F)
Soft Polyvinyl 7 Mils Thick - 3/4" x 60'
Rolls Individually Wrapped & Labeled

Packed 20 Rolls Per Display Box
200 Rolls (10 Boxes) Per Case

Part #	Qty
3460PT	1 roll - Clam Shell
3460C	Box of 20 rolls
3460U	Case of 200 Rolls



#3460PT
Clam Shell Packed
PICO UL Electrical Tape
1 Roll/Pack

Dielectric Grease



#0099PT (#0099C)

Part #	Qty
0099A	50 Tubes
0099PT	1 Tube
0099C	1 Tube
0005-ZR	Jar of 50 Tubes

1/4 oz Tube Clear Dielectric Grease
Coats Electrical Connections & Light Bulbs
Protects Against Arcing & Corrosion
Keeps Moisture Out of Sensitive
Electrical Connections



#0005-ZR

Plastic Display Jar - 50 #0099 Grease Tubes
4" Wide x 6" Hexagon Jar

Shrink Tubing



Single Wall Shrink Tube

Waterproof Shrink Tube

INSTALLATION:
Slide Tubing Over Wire
Crimp Terminal On Wire
Apply Heat 230°F to 348°F
(110°C to 120°C)
Cool For Tough Insulation

Heat Shrink Tools Page 19



Tubing Measured
By Inside Diameter
Before Shrinking



SINGLE WALL SHRINK TUBING

Flexible Polyolefin Single Wall Tubing
Multi-Purpose & Flame Retardant
Shrink Ratio 2 to 1
Operating Temperature:
-67°F to 275°F (-55°C to 135°C)

BLACK			RED		
I.D.	Part #	Qty	Part #	Qty	
1/8"	8219AA	100'	--	--	
1/8"	8219A	4'	8250A	4'	
1/8"	8219C	4-6"	8250C	4-6"	
1/8"	8219PT	4-6"	8250PT	4-6"	
3/16"	8220AA	100'	--	--	
3/16"	8220A	4'	8251A	4'	
3/16"	8220C	4-6"	8251C	4-6"	
3/16"	8220PT	4-6"	8251PT	4-6"	
1/4"	8221AA	100'	8252AA	100'	
1/4"	8221A	4'	8252A	4'	
1/4"	8221C	4-6"	8252C	4-6"	
1/4"	8221PT	4-6"	8252PT	4-6"	
3/8"	8222AA	100'	8253AA	100'	
3/8"	8222A	4'	8253A	4'	
3/8"	8222C	4-6"	8253C	4-6"	
3/8"	8222PT	4-6"	8253PT	4-6"	
1/2"	8223AA	100'	--	--	
1/2"	8223A	4'	8254A	4'	
1/2"	8223C	4-6"	8254C	4-6"	
1/2"	8223PT	4-6"	8254PT	4-6"	
3/4"	8224AA	100'	--	--	
3/4"	8224A	4'	8255A	4'	
3/4"	8224C	4-6"	8255C	4-6"	
3/4"	8224PT	4-6"	8255PT	4-6"	
1"	8225AA	100'	--	--	
1"	8225A	4'	8256A	4'	
1"	8225C	4-6"	8256C	4-6"	
1"	8225PT	4-6"	8256PT	4-6"	

WATERPROOF SHRINK TUBING

Semi-Flexible Polyolefin Dual Wall
Inner Adhesive Wall Melts & Flows
While Outer Wall Shrinks
Moisture Proof Upon Cooling
Shrink Ratio 3 to 1
Operating Temperature:
-49°F to 257°F (-45°C to 125°C)

BLACK			RED		
I.D.	Part #	Qty	Part #	Qty	
1/8"	8229A	4'	--	--	
1/8"	8229C	4-6"	--	--	
1/8"	8229PT	4-6"	--	--	
3/16"	8230A	4'	8260A	4'	
3/16"	8230C	4-6"	8260C	4-6"	
3/16"	8230PT	4-6"	8260PT	4-6"	
1/4"	8231A	4'	8261A	4'	
1/4"	8231C	4-6"	8261C	4-6"	
1/4"	8231PT	4-6"	8261PT	4-6"	
3/8"	8232A	4'	8262A	4'	
3/8"	8232C	4-6"	8262C	4-6"	
3/8"	8232PT	4-6"	8262PT	4-6"	
1/2"	8233A	4'	8263A	4'	
1/2"	8233C	4-6"	8263C	4-6"	
1/2"	8233PT	4-6"	8263PT	4-6"	
3/4"	8234A	4'	8264A	4'	
3/4"	8234C	4-6"	8264C	4-6"	
3/4"	8234PT	4-6"	8264PT	4-6"	
1"	8235A	4'	8265A	4'	
1"	8235C	4-6"	8265C	4-6"	
1"	8235PT	4-6"	8265PT	4-6"	
1-1/4"	8236A	4'	8266A	4'	
1-1/4"	8236C	4-6"	8266C	4-6"	
1-1/4"	8236PT	4-6"	8266PT	4-6"	
1-1/2"	8237A	4'	8267A	4'	
1-1/2"	8237C	4-6"	8267C	4-6"	
1-1/2"	8237PT	4-6"	8267PT	4-6"	

SINGLE WALL SHRINK TUBING

Package of 6" or 2" Pieces
1/8" 3/16" 1/4" 3/8" Diameter Tubing

Part #	Qty
8226C	4-6"
8226H	10-2"
8226PT	4-6"
8226KT	10-2"
8226QT	5-2"



NEW