


# O'Rings



O'Rings are made of Buna N material - 70 Durometer Nitrile Rubber  
Resistant to mineral oil, hydraulic fluids, air, L.P. & natural gas.  
With pressure, O'Ring stretches & flows filling seal cavity  
At extremely low temperatures O'Ring becomes brittle, but still functions as a seal.  
Upon warming O'Ring will assume its flexible properties without harm.  
Prolonged exposure to excessive heat will cause O'Ring to permanently harden.

O'Rings Measured By Inside Diameter & Thickness  
Operating Temperature: -40°F to 275°F (-40°C to 135°C)  
Also Available in QT Clam Shell - Consult Price Sheet

*Kits Available  
(Page 2)*



I.D.	O.D.	Width	Part #	Qty	Part #	Qty	Part #	Qty
3/32"	7/32"	1/16"	10005A	1000	10005C	100	10005QT	10
1/8"	1/4"	1/16"	10006A	1000	10006C	100	10006QT	10
5/32"	9/32"	1/16"	10007A	1000	10007C	100	10007QT	10
3/16"	5/16"	1/16"	10008A	1000	10008C	100	10008QT	10
7/32"	11/32"	1/16"	10009A	1000	10009C	100	10009QT	10
1/4"	3/8"	1/16"	10010A	1000	10010C	100	10010QT	10
5/16"	7/16"	1/16"	10011A	1000	10011C	100	10011QT	10
3/8"	1/2"	1/16"	10012A	1000	10012C	100	10012QT	10
7/16"	9/16"	1/16"	10013A	1000	10013C	100	10013QT	10
1/2"	5/8"	1/16"	10014A	1000	10014C	100	10014QT	8
9/16"	11/16"	1/16"	10015A	1000	10015C	100	10015QT	8
5/8"	3/4"	1/16"	10016A	1000	10016C	100	10016QT	8
11/16"	13/16"	1/16"	10017A	1000	10017C	100	10017QT	8
3/8"	9/16"	3/32"	10110A	1000	10110C	100	10110QT	8
7/16"	5/8"	3/32"	10111A	1000	10111C	100	10111QT	8
1/2"	11/16"	3/32"	10112A	1000	10112C	100	10112QT	8
9/16"	3/4"	3/32"	10113A	1000	10113C	100	10113QT	8
5/8"	13/16"	3/32"	10114A	500	10114C	50	10114QT	8
11/16"	7/8"	3/32"	10115A	500	10115C	50	10115QT	8
3/4"	15/16"	3/32"	10116A	500	10116C	50	10116QT	8

I.D.	O.D.	Width	Part #	Qty	Part #	Qty	Part #	Qty
3/4"	1"	1/8"	10210A	250	10210C	25	10210QT	5
13/16"	1-1/16"	1/8"	10211A	250	10211C	25	10211QT	5
7/8"	1-1/8"	1/8"	10212A	250	10212C	25	10212QT	5
15/16"	1-3/16"	1/8"	10213A	250	10213C	25	10213QT	5
1"	1-1/4"	1/8"	10214A	250	10214C	25	10214QT	5
1-1/16"	1-5/16"	1/8"	10215A	250	10215C	25	10215QT	4
1-1/8"	1-3/8"	1/8"	10216A	250	10216C	25	10216QT	4
1-3/16"	1-7/16"	1/8"	10217A	250	10217C	25	10217QT	4
1-1/4"	1-1/2"	1/8"	10218A	200	10218C	25	10218QT	4
1-5/16"	1-9/16"	1/8"	10219A	200	10219C	25	10219QT	4
1-3/8"	1-5/8"	1/8"	10220A	150	10220C	15	10220QT	2
1-7/16"	1-11/16"	1/8"	10221A	150	10221C	15	10221QT	2
1-1/2"	1-3/4"	1/8"	10222A	150	10222C	15	10222QT	2
1-5/8"	1-7/8"	1/8"	10223A	150	10223C	15	10223QT	2
1-3/4"	2"	1/8"	10224A	100	10224C	10	10224QT	2
1-7/8"	2-1/8"	1/8"	10225A	100	10225C	10	10225QT	2

# Vacuum Line Accessories

## CONNECTORS AND COUPLERS

High Impact Nylon Connectors  
Chemical Resistance  
Barbed To Hold Hose Without Clamps  
Colors May Vary  
Operating Temperature:  
-40°F to 250°F (-40°C to 121°C)



*Kits Available  
(Page 4)*



O.D.	Desc.	Part #	Qty
3/16"	3-Way	5225A	100
3/16"	3-Way	5225C	10
3/16"	3-Way	5225PT	10



O.D.	Desc.	Part #	Qty
3/16"	5-Way	5229A	50
3/16"	5-Way	5229C	2
3/16"	5-Way	5229PT	2

## "T" CONNECTORS

O.D.	Part #	Qty	Part #	Qty
1/8"	5231A	200	5231PT	25
1/8"	5231C	25	5231QT	1
1/8"	5231D	3	—	—
3/16"	5232A	200	5232PT	25
3/16"	5232C	25	5232QT	1
3/16"	5232D	3	—	—
1/4"	5233A	100	5233PT	10
1/4"	5233C	10	5233QT	1
1/4"	5233D	2	—	—
5/16"	5234A	100	5234PT	10
5/16"	5234C	10	5234QT	1
5/16"	5234D	2	—	—
3/8"	5235A	100	5235PT	5
3/8"	5235C	5	—	—

## COUPLERS

O.D.	Part #	Qty	Part #	Qty
1/8"	5241A	300	5241PT	25
1/8"	5241C	25	5241QT	1
1/8"	5241D	3	—	—
3/16"	5242A	300	5242PT	25
3/16"	5242C	25	5242QT	1
3/16"	5242D	3	—	—
1/4"	5243A	200	5243PT	20
1/4"	5243C	20	5243QT	1
1/4"	5243D	3	—	—
5/16"	5244A	100	5244PT	15
5/16"	5244C	15	5244QT	1
5/16"	5244D	3	—	—

## VACUUM TUBING / WIPER TUBING



Withstands Heat, Washer Solutions, Oil, Grease  
Vacuum Operated Accessories - Windshield Washer  
Emission Control Applications  
EPDM Operating Temperature -40°F to 180°F

Tubing I.D.	Connector O.D.	Part #	Qty	Part #	Qty	Part #	Qty
7/64"	1/8"	5161A	50'	5161C	6'	5161PT	6'
5/32"	3/16"	5162A	50'	5162C	5'	5162PT	5'
7/32"	1/4"	5163A	50'	5163C	4'	5163PT	4'
9/32"	5/16"	5164A	50'	5164C	3'	5164PT	3'

## UNIVERSAL "T" CONNECTOR & COUPLER

ABS Plastic Connectors - Temperature Range up to 250°F (121°C)  
Ends Fit 1/8", 3/16" or 5/16" Hose  
Barbed To Hold Hose Without Clamps



Desc.	Part #	Qty
"T"	5253A	50
"T"	5253C	1
"T"	5253PT	1

Desc.	Part #	Qty
Coupler	5254A	50
Coupler	5254C	1
Coupler	5254PT	1

# Carburetor Caps



Black EPDM Rubber Vacuum Caps  
Max Temperature 250°F (121°C)  
Available In Kit - #0002-HC (Page 4)

I.D.	Part #	Qty	Part #	Qty	Part #	Qty
1/8"	7030A	500	7030C	25	7030PT	25
3/16"	7031A	500	7031C	25	7031PT	25
1/4"	7032A	500	7032C	20	7032PT	20
5/16"	7033A	500	7033C	15	7033PT	15
3/8"	7034A	500	7034C	10	7034PT	10
Assorted Pack	7036C	10	7036PT	10		



Flexible Vinyl Tips  
Temperature Rating -22°F to 200°F

I.D.	Color	Part #	Qty	Part #	Qty	Part #	Qty
1/8"	Black	7020A	1000	7020C	50	7020KT	40
3/16"	White	7021A	1000	7021C	25	7021KT	20
1/4"	Red	7022A	1000	7022C	20	7022KT	13
5/16"	Blue	7023A	1000	7023C	15	7023KT	9
3/8"	Yellow	7024A	1000	7024C	10	7024KT	6
Assorted Pack		7029C	40	7029D	19	7029KT	17
Assorted Pack		7029M	9	7029PT	40	7029QT	9

*Kits Available  
(Page 4)*

