

Convolved Tubing & Accessories



Colored & Black Flexible Polyethylene Tubing
Tubing Split For Easy Wire Insertion
Operating Temperature -40°F to 185°F (-40°C to 85°C)



Black Polypropylene Connectors For Convolved Tubing
Accessories Measured By Tubing Diameter

OUTLET FITTING

Holds Loom Tight At Breakouts

Left - Right	Part #	Qty
1/2" - 1/2"	5107A	25
1/2" - 1/2"	5107C	1
1/2" - 1/2"	5107PT	1

I.D.	Color	Part #	Qty	Part #	Qty	Part #	Qty	Part #	Qty
1/8"	Black	5139AA	500'	5139A	50'	5139C	14'	5139PT	14'
1/4"	Black	5140AA	500'	5140A	50'	5140C	14'	5140PT	14'
1/4"	Red	5150AA	500'	5150A	50'	5150C	14'	5150PT	14'
3/8"	Black	5141AA	500'	5141A	50'	5141C	10'	5141PT	10'
1/2"	Black	5142AA	500'	5142A	50'	5142C	7'	5142PT	7'
5/8"	Black	5144AA	250'	5144A	50'	5144C	6'	5144PT	6'
3/4"	Black	5143AA	250'	5143A	50'	5143C	5'	5143PT	5'
1"	Black	5145AA	100'	—	—	—	—	—	—
1-1/4"	Black	5146AA	100'	—	—	—	—	—	—
1-1/2"	Black	5147AA	50'	—	—	—	—	—	—
2"	Black	5148AA	50'	—	—	—	—	—	—
Assorted Size		0006-CV1	Total 42'	Package of 1/4", 3/8", 1/2", 5/8", 3/4"					

NEW

TEE FITTING

Allows For Continuous Coverage Of Breakout Wires With Tubing



Left-Center-Right	Part #	Qty
3/8" - 3/8" - 3/8"	5110A	25
3/8" - 3/8" - 3/8"	5110C	1
3/8" - 3/8" - 3/8"	5110PT	1
1/2" - 1/2" - 1/2"	5111A	25
1/2" - 1/2" - 1/2"	5111C	1
1/2" - 1/2" - 1/2"	5111PT	1
3/4" - 3/8" - 3/4"	5112A	25
3/4" - 3/8" - 3/4"	5112C	1
3/4" - 3/8" - 3/4"	5112PT	1
3/4" - 1/2" - 3/4"	5113A	25
3/4" - 1/2" - 3/4"	5113C	1
3/4" - 1/2" - 3/4"	5113PT	1


High Temp Convolved Tubing



Flexible Black Nylon Tubing
With Blue/Gray Stripe
Tubing Split For Easy Wire Insertion
Temperature Rating:
-40°F to 300°F (-40°C to 149°C)

I.D.	Part #	Qty	Part #	Qty
1/4"	5170AA	500'	5170A	100'
3/8"	5171AA	500'	5171A	100'
1/2"	5172AA	500'	5172A	100'
5/8"	5173AA	250'	5173A	100'
3/4"	5174AA	250'	5174A	100'

Spi Wrap



(Wire Not Included)

Expandable Spiral Cut Flexible Polyethylene (LLDPE) Wrap
Retains Strength Under Repeated Flexing
Measured By Outside Diameter Of Unexpanded Wrap
Operating Temperature: -105°F to 215°F (-76°C to 102°C)
Natural Color

Fabric Loom



Flexible For Easy Wire Insertion
Saturated With Asphalt Compound
For Moisture Proof
Fabric Protects Against Short Circuits
Maximum Temperature 350°F (177°C)


I.D.	Part #	Qty	Part #	Qty
3/16"	8212A	250'	8212S	50'
1/4"	8213A	250'	8213S	50'
1/4"	8213C	10'	8213PT	10'
5/16"	8211A	250'	8211S	50'
3/8"	8214A	250'	8214S	50'
3/8"	8214C	7'	8214PT	7'
1/2"	8215A	250'	8215S	50'
1/2"	8215C	5'	8215PT	5'
5/8"	8216A	250'	8216S	50'
3/4"	8217A	250'	8217S	25'
1"	8218A	250'	8218S	25'

PACKAGE OF ASSORTED SPI WRAP SIZES

Part #	Qty
5126C	15'
5126PT	15'

O.D.	Part #	Qty	Part #	Qty
1/8"	5118A	100'	—	—
3/16"	5119A	100'	—	—
1/4"	5120A	100'	—	—
1/4"	5120C	5'	5120PT	5'
3/8"	5121A	100'	—	—
3/8"	5121C	5'	5121PT	5'
1/2"	5122A	100'	—	—
1/2"	5122C	5'	5122PT	5'
3/4"	5123A	100'	—	—
1"	5124A	100'	—	—

Grommets



A - O.D. of Wire or Wires
B - I.D. of Predrilled Hole
C - Groove/Wall Thickness

Flexible Oil Resistant Grommets
Insert Into Predrilled Holes
Guard Against Cut & Frayed Wires
Operating Temperature -31°F to 160°F (-35°C to 71°C)

ASSORTED GROMMET PACK

Part #	Qty
6110C	15
6110PT	15
6126QT	6

Kits Available
(Page 2)



A	B	C	Part #	Qty	Part #	Qty	Part #	Qty	Part #	Qty
1/8"	1/4"	1/16"	6115A	1000	6115D	20	6115PT	50	6115QT	7
1/8"	1/4"	1/16"	6115C	50	6115M	7	6115KT	20	—	—
3/16"	5/16"	1/16"	6116A	1000	6116D	18	6116PT	50	6116QT	6
3/16"	5/16"	1/16"	6116C	50	6116M	6	6116KT	18	—	—
1/4"	3/8"	1/16"	6117A	500	6117D	15	6117PT	50	6117QT	5
1/4"	3/8"	1/16"	6117C	50	6117M	5	6117KT	15	—	—
5/16"	7/16"	1/16"	6118A	500	6118D	10	6118PT	40	6118QT	5
5/16"	7/16"	1/16"	6118C	40	6118M	5	6118KT	10	—	—
3/8"	1/2"	1/16"	6119A	500	6119D	10	6119PT	40	6119QT	5
3/8"	1/2"	1/16"	6119C	40	6119M	5	6119KT	10	—	—
1/2"	5/8"	1/16"	6120A	250	6120D	8	6120PT	20	6120QT	3
1/2"	5/8"	1/16"	6120C	20	6120M	3	6120KT	7	—	—
7/16"	11/16"	1/8"	6121A	250	6121D	5	6121PT	15	6121QT	2
7/16"	11/16"	1/8"	6121C	15	6121M	2	6121KT	4	—	—
5/8"	7/8"	1/16"	6122A	100	6122D	4	6122PT	10	6122QT	2
5/8"	7/8"	1/16"	6122C	10	6122M	2	6122KT	3	—	—
11/16"	1"	1/16"	6123A	100	6123D	2	6123PT	5	6123QT	1
11/16"	1"	1/16"	6123C	5	6123M	1	6123KT	2	—	—
3/4"	1-1/16"	1/8"	6124A	100	6124D	2	6124PT	4	6124QT	1
3/4"	1-1/16"	1/8"	6124C	4	6124M	1	6124KT	2	—	—
1/2"	13/16"	1/4"	6125A	100	6125D	4	6125PT	6	6125QT	1
1/2"	13/16"	1/4"	6125C	6	6125M	2	6125KT	2	—	—
1"	1-3/8"	1/8"	6127A	25	6127C	3	6127PT	3	—	—

All Items with QT, KT, GT or PT Suffix are Clam Shell Program Items.